Printing date 02.08.2013

Version number 2

Revision: 02.08.2013

Not classified as hazardous according to criteria of Australian Safety and Compensation Council

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

- · Trade name: Hilti OneStep-Anchor T 15 / N 15
- Container size Rock anchor HOS-A 120 300
- \cdot Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- Application of the substance / the preparation

Rock anchor for the stabilization of tunnels, galleries and the like in mining.

The Hilti OneStep-Anchor is classified as an article in accordance with section 3, paragraph 5, of the EC Chemicals Bill. The product is not subject to identification regulations under EC Directives and the Ordinance on Hazardous Materials.

· Details of the supplier of the safety data sheet

• **Manufacturer/Supplier:** Hilti (Aust.) Pty. Ltd. Level 5, 1G Homebush Bay Drive Rhodes N.S.W. 2138 Australia Phone: 131 292 Fax: 1300 135 042 Email: serviceaustralia@hilti.com

 Informing department: see section 16
 Emergency telephone number: Schweizerisches Toxikologisches Informationszentrum - 24 h Service Tel.: 0041 / 44 251 51 51 (international)

Hilti (Aust.) Pty. Ltd. Phone: 131 292 Fax: 1300 135 042

2 Hazards identification

· Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

In accordance with article 3 (3) of REACH, this / these item(s) are products.

- A product is not subject to the mandatory marking regulations applicable to dangerous substances.
- (Arnsberg District Government AZ 84.12.22.67-2003-7)

Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed The product is not classified as hazardous to health or environment according to the CLP regulation.

· Label elements

| Laber cicilient | |
|---|--|
| Labelling according | ording to Regulation (EC) No 1272/2008 Void |
| Hazard pictog | rams Void |
| Signal word V | <i>'oid</i> |
| · Hazard staten | nents Void |
| · Precautionary | y statements |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P235 | Keep cool. |
| P262 | Do not get in eyes, on skin, or on clothing. |
| P260 | Do not breathe vapours. |
| P305+P351+P3 | 338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and |
| | easy to do. Continue rinsing. |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water. |
| · Other hazards | 3 |
| · Results of PB | Γ and vPvB assessment |
| • PBT: Not appl | icable. |
| • vPvB: Not app | licable. |
| | |

(Contd. on page 2)

AU EN



Version number 2

Revision: 02.08.2013

Trade name: Hilti OneStep-Anchor T 15 / N 15

(Contd. of page 1)

| | haracterization: Mixtures | |
|---------------|--|---------|
| Description | : | |
| Rock anchor | with internally integrated 2-component foil pack. | |
| The foil pack | k unit contains: | |
| Unsaturated | polyester resin with styrene, acrylate, filler materials | |
| | d dibenzoyl peroxide as a paste, filler materials | |
| Dangerous | components: | |
| 100-42-5 | styrene | <12.5% |
| | 🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 | |
| 15625-89-5 | Trimethylolpropane triacrylate | 2.5-10% |
| | () Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 | |
| 94-36-0 | dibenzoyl peroxide | <2.5% |
| | 🔗 🕐 Org. Perox. B, H241; 🕚 Eye Irrit. 2, H319; Skin Sens. 1, H317 | |
| 99-97-8 | N,N-dimethyl-p-toluidine | <1% |
| | Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Acute Chronic 3, H412 | |

4 First aid measures

· Description of first aid measures

- · General information
- First aid measures only required by release of ingredients or generation of decomposition products. Instantly remove any clothing soiled by the product.
- · After inhalation Take affected persons into the open air and position comfortably
- After skin contact Instantly wash with water and soap and rinse thoroughly. If skin irritation persist, call a physician.
- · After eye contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
- After swallowing Rinse out mouth and then drink plenty of water.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents

Water spray, carbon dioxide (CO2), carbon dioxide blanket, foam, or dry powder. Sand

- · For safety reasons unsuitable extinguishing agents Water with full jet.
- · Special hazards arising from the substance or mixture
- Can be released in case of fire
- Carbon monoxide (CO)
- Carbon dioxide (CO2)
- Nitrogen oxides (NOx)
- Under certain fire conditions, traces of other toxic gases cannot be excluded.
- · Advice for firefighters
- · Protective equipment: In the event of fire, wear self contained breathing apparatus

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective clothing. Keep away from ignition sources
- Environmental precautions: Do not allow to enter the ground/soil.
- · Methods and material for containment and cleaning up: Collect mechanically. Remove remainders with solvent and liquid-binding material.

Dispose of the material collected according to regulations.



Version number 2

Revision: 02.08.2013

(Contd. of page 2)

Trade name: Hilti OneStep-Anchor T 15 / N 15

· Reference to other sections

See Section 7 for information on safe handling

- See Section 8 for information on personal protection equipment.
- See Section 13 for information on disposal.

7 Handling and storage

· Handling

· Precautions for safe handling

Observe expiry date. Keep ignition sources away - Do not smoke.

Do not disassemble the OneStep bolt

- · Information about protection against explosions and fires:
- keep away from heat and direct sunlight
- Keep ignition sources away Do not smoke.
- \cdot Conditions for safe storage, including any incompatibilities
- \cdot Storage
- · Requirements to be met by storerooms and containers:

Keep in a cool, dry and dark place; -20 °C to 25 °C.

Please attend to the local storage regulations for underground mining operations

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Please attend to the local storage regulations for underground mining operations

- Protect from heat and direct sunlight.
- **Specific end use**(*s*) Rock anchor for stabilizing tunnels, galleries and the like.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

100-42-5 styrene (<12.5%)

NES (Australia) Short-term value: 426 mg/m³, 100 ppm

Long-term value: 213 mg/m³, 50 ppm

• Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

- · Personal protective equipment
- General protective and hygienic measures
- The usual precautionary measures should be adhered to general rules for handling chemicals.
- Do not eat, drink or smoke while working.
- Keep away from foodstuffs, beverages and food.
- Wash hands during breaks and at the end of the work.
- Avoid contact with the eyes and skin.
- Take off immediately all contaminated clothing
- Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)



Version number 2

Revision: 02.08.2013

(Contd. of page 3)

Trade name: Hilti OneStep-Anchor T 15 / N 15



Protective work clothing.

9 Physical and chemical properties

| Information on basic physical and o | chemical properties | |
|--|--|--|
| General Information | | |
| · Appearance: | Calf duilling analysis interpreted dual fail much inside | |
| Form: Colour: | Self drilling anchor – integrated dual foil pack inside | |
| Colour: | foil package | |
| · Odour: | grey-green-white Aromatic | |
| · Odour: · Odour threshold: | Not determined | |
| | | |
| · pH-value: | Not applicable | |
| · Change in condition | | |
| Melting point/Melting range: | Not determined | |
| Boiling point/Boiling range: | Not determined | |
| · Flash point: | 31 °C (DIN 53213) | |
| · Inflammability (solid, gaseous) | Not determined | |
| · Ignition temperature: | 350 °C (TMPTA) | |
| · Decomposition temperature: | Not determined | |
| · Self-inflammability: | Product is not selfigniting. | |
| · Danger of explosion: | Product is not explosive. | |
| · Critical values for explosion: | | |
| Lower: | 1.2 Vol % (Styrene) | |
| Upper: | 8.9 Vol % (Styrene) | |
| · Vapour pressure at 20 °C: | 7.1 hPa (Styrene) | |
| · Density | Not determined | |
| · Relative density | Not applicable | |
| · Vapour density | Not applicable | |
| · Evaporation rate | Not applicable | |
| · Solubility in / Miscibility with | | |
| Water: | Not miscible or difficult to mix | |
| \cdot Partition coefficient (n-octanol/wat | er): Not applicable | |
| · Viscosity: | | |
| dynamic: | Not applicable | |
| kinematic: | Not applicable | |
| • Other information | No further relevant information available. | |

(Contd. on page 5)



Version number 2

Revision: 02.08.2013

Trade name: Hilti OneStep-Anchor T 15 / N 15

(Contd. of page 4)

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- \cdot Thermal decomposition / conditions to be avoided:
- Non-observance of the specified storage conditions (see section 7) will lead to gradual decomposition of the dibenzoylperoxide. This will make the product unusable.
- To avoid thermal decomposition do not overheat.
- No decomposition if used and stored according to specifications.
- \cdot Possibility of hazardous reactions No dangerous reactions known
- \cdot Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- \cdot Hazardous decomposition products: No dangerous decomposition products known

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- \cdot on the skin: No irritant effect.
- · on the eye: No irritant effect.
- \cdot Sensitization: No sensitizing effect known.
- \cdot CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) None

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- According to recipe contains the following heavy metals and compounds according to EC guideline NO. 76/464 EC:
- None
- · General notes: The product does not contain organically bounded halogens (AOX-free).
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Unusable anchors must be collected separately. For disposal, local regulations issued by the authorities must be observed.

Consult the manufacturer if necessary.

For disposal, local regulations issued by the authorities must be observed.

- · Uncleaned packagings:
- · Recommendation:
- Non contaminated packagings can be reused.

Dispose of packaging according to regulations on the disposal of packagings.

14 Transport information

· UN-Number

· ADG, ADN, IMDG, IATA

Void

(Contd. on page 6)



Version number 2

Revision: 02.08.2013

Trade name: Hilti OneStep-Anchor T 15 / N 15

| | (Contd. of page |
|--|--|
| · UN proper shipping name · ADG, ADN, IMDG, IATA | Void |
| · Transport hazard class(es) | |
| · ADG, ADN, IMDG, IATA · Class | Void |
| · Packing group · ADG, IMDG, IATA | Void |
| · Environmental hazards: · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| • Transport in bulk according to Annex MARPOL73/78 and the IBC Code | II of Not applicable. |
| · Transport/Additional information: | Not dangerous according to the above specifications. Assessment BAM Nr. II.2-1061 2/02 and Nr. II.2-324/03, Nr. II.2-135/09 |
| · UN "Model Regulation": | - |

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

All ingredients are listed.

| · Standard for the Uniform Scheduling of Drugs and Poisons | | | |
|--|--------------------|------------|--|
| 100-42-5 | styrene | \$5 | |
| 94-36-0 | dibenzoyl peroxide | S2, S4, S5 | |

· National regulations

· Information about limitation of use: Employment restrictions concerning young persons must be observed. · Chemical safety assessment: not required.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H241 Heating may cause a fire or explosion.
- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects. · Department issuing data specification sheet: Hilti Entwicklungsgesellschaft mbH Hiltistrasse 6 D-86916 Kaufering Tel.: +49 8191 906310 Fax: +49 8191 90176310 e-mail: anchor.hse@hilti.com · Contact: Mechthild Krauter · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods



Version number 2

Revision: 02.08.2013

Trade name: Hilti OneStep-Anchor T 15 / N 15

IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

 \cdot * Data compared to the previous version altered.

(Contd. of page 6)

AU EN