

Version number 1

Revision: 26.01.2015

Not classified as hazardous according to criteria of Australian Safety and Compensation Council

Identification	of the substance/mixture and of the company/undertaking
Product identif	ier
<b>Relevant identi</b> Article categor	iMH BatteriesFB 105 / SFB 125 / SFB 126 / SFB 155 / SFB 185 / B 24/3,0SA 80 / PRA 801 / PRA 82 / PRA 810 / PRA 87 / PPA 82Fied uses of the substance or mixture and uses advised againsty AC3 Electrical batteries and accumulatorshe substance / the mixture Rechargeable NiMH battery pack for electric tools
<b>Details of the su Manufacturer</b> / Hilti (Aust.) Pty	<b>upplier of the safety data sheet Supplier:</b> . Ltd. nebush Bay Drive
Phone: 131 292 Fax: 1300 135 0 Email: serviceau	42 stralia@hilti.com
	i.com
Hilti (Aust.) Pty Phone: 131 292 Fax: 1300 135 0	.Ltd.
Hazards ident	ification
Classification o	f the substance or mixture ot classified according to the Globally Harmonised System (GHS).
GHS label elem Hazard pictogr Signal word Vo Hazard statem	<b>ams</b> Void id
pressures encour explosion and cl It may cause hea	hemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and netered during normal use. As a result, during normal use there is no physical danger of ignition or nemical danger of hazardous materials leakage. It generation or electrolite leakage if battery terminals contact with other metals. Elektrolyte is flammab objet leakage move the battery from fire immediately.
	used to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release rated. The battery case will be breaked at the extreme, hazardous materials may be released.
Composition/	nformation on ingredients
	actorization. Mixtures
Chemical chara	acterisation, mixtures
• <b>Chemical chara</b> • <b>Description:</b> Rechargeable N Name/type	MH battery pack: no. of cells energy capacity [Wh]

(Contd. on page 2)



Safety data sheet according to NOHSC:2011 (2003) / ISO 11014 Version number 1

Revision: 26.01.2015

(Contd. of page 1)

SFB 105 / SFB 125 / SFB 126 / SFB 155 / SFB 185 / B 24/3,0 PSA 80 / PRA 801 / PRA 82 / PRA 810 / PRA 87 / PPA 82	Trade name: NiMH Batteries		
PSA 80 / PRA 801 / PRA 82 / PRA 810 / PRA 87 / PPA 82	SFB 105 / SFB 125 / SFF	B 126 / SFB 155 / SFB 185 / B	24/3,0
	PSA 80 / PRA 801 / PR	RA 82 / PRA 810 / PRA 87 / PH	PA 82

SFB 155	13	46,8
SFB 185	15	54
B 24/3,0	20	72
PSA 80	4	19,2
PRA 801	3	30,6
PRA 82	2	19,2
PRA 810	3	42
PRA 87	4	44
PPA 82	4	32

This product contains a positive electrode (Nickel(III)-oxidehydroxide), a negative electrode (metallhydride powder) and electrolyte (potassium hydroxide / sodium hydroxide).

The physical form of the product, however, precludes exposure to workers under normal conditions of use.

12054-48-7	nickel dihydroxide	0-20%
	Resp. Sens. 1, H334; Muta. 2, H341; Carc. 1A, H350; Repr. 1B, H360; STOT RE 1, H372; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317	
	NiOOH	1-22%
	MmNiCoMnAl	2-34%
	(MmNiCoMnAl)Hx	3-35%
1310-58-3	potassium hydroxide Skin Corr. 1A, H314; Acute Tox. 4, H302	0-4%
1310-73-2	sodium hydroxide Skin Corr. 1A, H314	0-4%

For the wording of the listed risk phrases refer to section 16.

For the wording of the listed risk phrases refer to section 16.

# 4 First aid measures

- $\cdot$  Description of first aid measures
- · General information

This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following measures have to be taken.

- $\cdot$  **After inhalation** Take affected persons into the open air and position comfortably
- After skin contact Instantly wash with water and soap and rinse thoroughly. If skin irritation persist, call a physician.
- · After eye contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
- · After swallowing
- Rinse out mouth and then drink plenty of water.
- Do not induce vomiting; immediately call for medical help.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **5** Firefighting measures

- $\cdot$  Extinguishing media
- · Suitable extinguishing agents

Water spray, carbon dioxide (CO2), carbon dioxide blanket, foam, or dry powder.

- Dry sand
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment:

In the event of fire, wear self contained breathing apparatus

(Contd. on page 3)



Version number 1

Revision: 26.01.2015

Trade name: NiMH Batteries

 SFB 105 / SFB 125 / SFB 126 / SFB 155 / SFB 185 / B 24/3,0
 PSA 80 / PRA 801 / PRA 82 / PRA 810 / PRA 87 / PPA 82

(Contd. of page 2)

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources
- $\cdot$  Environmental precautions: Do not allow to enter the ground/soil.
- **Methods and material for containment and cleaning up:** Collect mechanically. Dilute with much water.

### · Reference to other sections

- See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.
- See Section 13 for information on disposal.

### 7 Handling and storage

### · Handling

- **Precautions for safe handling** Do not soak in water or seawater.
- Do not expose to strong oxidizers.
- Do not give a strong mechanical shock or fling.
- Never disassemble, modify or deform.
- Do not connect the positive terminal to the negative terminal with electrically conductive material.
- Use only the chargers / electric tools specified by Hilti to charge or discharge the battery.
- $\cdot$  Information about protection against explosions and fires:
- Do not throw into fire or expose to high temperatures (>85 °C).
  - Do not connect the positive terminal to the negative terminal with electrically conductive material.
- $\cdot$  Conditions for safe storage, including any incompatibilities
- · Storage
- **Requirements to be met by storerooms and containers:** Avoid direct sunlight, high temperature, high humidity. Store in a cool place (temperature: -20 °C ~ 35 °C, humidity: 45 - 85%)
- **Information about storage in one common storage facility:** Store away from water.
- Do not store together with electrically conductive materials.
- Further information about storage conditions:
  Further information about storage conditions:
  The accu-pack should be stored at 30 to 50% of the charging capacity.
  Avoid storing in places where it is exposed to static electricity.
  Protect from heat and direct sunlight.
  Protect from humidity and keep away from water.
- · Storage class
- As per VCI (1991) storage classification concept.
- 11

• Specific end use(s) To be used only for the intended purpose. Please refer to the operating instructions.

### 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- $\cdot$  Components with limit values that require monitoring at the workplace:
- No technical measures are necessary during normal use. In case of leakage of substances contained within the cell, the information below may be useful.
- · Additional information: The lists that were valid during the compilation were used as basis.
- · Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to general rules for handling chemicals.


(Contd. on page 4)

AUEN



Version number 1

Revision: 26.01.2015



Appearance.
Form:
Colour:
· Odour:
· Odour threshold:

Colour:	Black / Red
· Odour:	Odourless
· Odour threshold:	Not determined.
· pH-value:	Not applicable
<ul> <li>Change in condition Melting point/Melting range: Boiling point/Boiling range:</li> </ul>	Not applicable Not applicable
· Flash point:	Not applicable
· Inflammability (solid, gaseous)	Not determined.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive.
· Critical values for explosion: Lower: Upper:	Not determined. Not determined.
· Vapour pressure:	Not applicable.
· Density · Relative density	Not applicable Not determined.
	(Contd. on page 5

plastic case





Version number 1

Revision: 26.01.2015

## Trade name: NiMH Batteries

# SFB 105 / SFB 125 / SFB 126 / SFB 155 / SFB 185 / B 24/3,0 PSA 80 / PRA 801 / PRA 82 / PRA 810 / PRA 87 / PPA 82

		(Contd. of page 4
· Vapour density	Not applicable.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with	h	
Water:	Unsoluble	
· Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
dynamic:	Not applicable.	
kinematic:	Not applicable.	
· Solvent content:		
Organic solvents:	0.0 %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

In the event of misuse of a battery cell or the like, oxygen or hydrogen accumulates in the cell and the cell's internal pressure rises. These gases may be emitted through the gas release vent. The gases may ignite if in the proximity of a naked flame or source of ignition.

· Conditions to avoid

Do not connect the positive terminal to the negative terminal with electrically conductive material.

Do not overcharge.

Protect from heat and direct sunlight.

Protect from humidity and keep away from water.

· Incompatible materials: Conductive materials, water, seawater, strong oxidizers and strong acids.

 $\cdot$  Hazardous decomposition products: Acrid or harmful gas is emitted during fire

# **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- on the skin:

This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact:

- Caustic effect on skin and mucous membranes.
- $\cdot$  on the eye: Strong irritant with the danger of severe eye injury.
- $\cdot$  Sensitisation: No sensitizing effect known.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) None

# **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Do not allow battery packs to penetrate the soil.
- The battery cell may corrode and electrolyte may leak.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 6)



Version number 1

Revision: 26.01.2015

**Trade name: NiMH Batteries** 

SFB 105 / SFB 125 / SFB 126 / SFB 155 / SFB 185 / B 24/3,0 PSA 80 / PRA 801 / PRA 82 / PRA 810 / PRA 87 / PPA 82

(Contd. of page 5)

· Other adverse effects No further relevant information available.

### **13 Disposal considerations**

· Waste treatment methods

· Recommendation Dispose of this battery pack according to national regulations or return the used battery pack to Hilti.

· European waste catalogue

16 06 05 other batteries and accumulators

20 01 34 batteries and accumulators other than those mentioned in 20 01 33

· Uncleaned packagings:

· Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

Transport information	
· UN-Number · ADG, IMDG, IATA · ADN	UN3496 not applicable
· UN proper shipping name · ADG, IMDG, IATA	Batteries, nickel-metal hydride
· Transport hazard class(es)	
· ADG, IMDG, IATA · Class	9 Miscellaneous dangerous substances and articles.
· Packing group · ADG	Void
· Environmental hazards: · Marine pollutant:	No
Special precautions for user EMS Number:	Warning: Miscellaneous dangerous substances and articles. F-A,S-I
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	
· IMDG	Special Provision 963
· IATA	Special Provision A199
· UN "Model Regulation":	UN3496, Batteries, nickel-metal hydride

### **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· Chemical safety assessment: not required.

### **16 Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

(Contd. on page 7)

AUEN

AU EN



• \* Data compared to the previous version altered.

# Safety data sheet according to NOHSC:2011 (2003) / ISO 11014

Printing date 02.06.2015	Version number 1	<b>Revision: 26.01.2015</b>
	125 / SFB 126 / SFB 155 / SFB 185 / B 24 801 / PRA 82 / PRA 810 / PRA 87 / PPA	
H341 Suspected of causing ge H350 May cause cancer. H360 May damage fertility or	thma symptoms or breathing difficulties if inhaled. enetic defects. • the unborn child. as through prolonged or repeated exposure. fe.	(Contd. of page 6)
<ul> <li>Department issuing data spe Hilti Entwicklungsgesellschaf Hiltistrasse 6</li> <li>D-86916 Kaufering Tel.: +49 8191 906310</li> <li>Fax: +49 8191 90176310</li> <li>e-mail: anchor.hse@hilti.com</li> <li>Contact: Mechthild Krauter</li> </ul>	τ mbH	
of Dangerous Goods by Rail) ICAO: International Civil Aviation Of ADR: Accord européen sur le transpor Goods by Road) IMDG: International Maritime Code fi IATA: International Air Transport Ass EINECS: European Inventory of Exist ELINCS: European List of Notified C CAS: Chemical Abstracts Service (div Acute Tox. 4: Acute toxicity, Hazard G Skin Corr. 1A: Skin corrosion/irritation Skin Irrit. 2: Skin corrosion/irritation Skin Irrit. 2: Sensitisation - Respirat Skin Sens. 1: Sensitisation - Skin, Haz Muta. 2: Germ cell mutagenicity, Hazard Ca Repr. 1B: Reproductive toxicity, Hazard Ca STOT RE 1: Specific target organ toxi Aquatic Acute 1: Hazardous to the aqu	ant le transport des marchandises dangereuses par chemin de fer (Regulati- rganisation rt des marchandises dangereuses par Route (European Agreement concerni or Dangerous Goods sociation ing Commercial Chemical Substances hemical Substances 'ision of the American Chemical Society) Category 4 n, Hazard Category 1A Hazard Category 2 ., Hazard Category 1 ard Category 1 ard Category 1 ard Category 1 rd Category 1B licity - Repeated exposure, Hazard Category 1 latic environment - AcuteHazard, Category 1 iquatic environment - Chronic Hazard, Category 1	· ·